

Polyvinyl Chloride -PVC Safety Spray Shields

For Containing and
Detecting Hazardous
Leaks and Sprays

Protects personnel,
Equipment, and the
Environment



Safety Spray Shields are designed to prevent a catastrophe by temporarily containing hazardous leaks and sprays. Leaks can occur on piping systems conveying chemicals, high temperature fluids, and steam, which can harm workers, damage nearby equipment, and the environment.

Leaks of flammables, such as fuel or oil, can create fire and explosion hazards.

In all cases Metal Spray shields must be used on flammable oils and fuels.

- Safety Spray Shields help meet regulatory standards set by agencies such as OSHA, EPA, MSHA, SOLAS, ABS, and DNV, and are now required by some insurance companies.

Designed to fit:

Flanges – Valves - Expansion Joints – Fittings - Flexible Hoses – Pipe - Sight Glasses – Manholes – Instruments – Pumps and custom applications

The PVC Spray Shields supplied by Klinger are constructed of durable fabrics that are chemical and weather resistant.

- PVC spray shields are manufactured from an orange coloured material as standard or in a Clear PVC material. They are also available in the orange PVC with a clear PVC centre strip. This allows for complete visual inspection as would be the case for the Clear PVC.
- Our Shields are ready to install quickly and simply by one person with the equipped hook and loop fasteners and draw cord.
- We offer Shields for all sizes and ratings, both standard, non-standard, and metric (DN).
- We are able to provide problem solving solutions by designing and manufacturing custom shields for special sizes and applications.

PVC spray shield specification:



PVC standard

- Reinforced polyvinyl chloride fabric.
- Multi-layered construction.
- Tough poly thread and draw cord.
- Standard colour is safety orange. Yellow and other colours available upon request.
- Maximum operating temperature of 76 deg C.
- Also available with a PVC Clear centre strip and entire Clear PVC models which provide visual inspection



PVC
Clear window



PVC Clear

Klinger Limited contact details:

Telephone: 1300 798 279 or +61 8 92511600 Facsimile: +61 (08) 9358 9286

[Email local: sales@klinger.com.au](mailto:sales@klinger.com.au)

Email exports: export@klinger.com.au

www.klinger.com.au